

JBC



FL FLUX

Reference Guide

www.jbctools.com

CONTENTS



FL is a liquid flux water based designed to be used in the preparation of printed circuits prior to soldering an SMD component, especially flat pack integrated circuits.

“NON RESIDUE” Classified Flux.

HOWTO USE

- 1- Clean and degrease the surfaces to be welded.
- 2- Use the brush to apply the flux to the integrated circuit pads.
- 3- Do the solder.
- 4- Flux remains are inert, do not cause electrical or chemical problems. If you want to remove it, use water for cleaning them. Therefore it is a product respectful with the environment.

SAFETY INSTRUCTIONS

- Wear protection glasses and gloves during handling.
- Irritating to eyes and skin in case of lengthy contact.
- Harmful in case of ingestion.
- Avoid contact with eyes.
- Do not eat or drink.
- In case of problems due to contact, ingestion or inhalation seek medical advice.
- Keep away from children.
- Wash your hands after its use.

HANDLING AND STORAGE

- Inside its container tightly closed at 20°C.
- Once opened, use within 6 months

TECHNICAL SPECIFICATIONS

COMPOSITION

Water: 95% min.

Organic activators: <3%

Tight-active agents: 1% max.



This product should not be
thrown in the garbage.



MORE INFORMATION
www.jbctools.com

0008825/0112